

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A key ~~cover for covering a head of a key, where the head~~
~~has an opening for receiving a key ring therethrough, said key cover~~ securement comprising:

a key;

a key ring; and

a key cover comprising:

a first sidewall defining a plane and terminating in a first edge, the first sidewall
having a first aperture ~~therethrough~~ extending through the first sidewall;

a second sidewall terminating in a second edge, the second sidewall having a
second aperture ~~therethrough~~ extending through the second sidewall;

an outer wall extending between the first and second sidewalls to define a recess
that receives the head of the key therein so that the opening in the head ~~is aligned~~ remains
aligned with the key cover only by the key ring passing simultaneously therethrough
wherein the outer wall having ends that are spaced apart from the first and second edges
of the first and second sidewalls, respectively; and

a tactile feature defining a rear contact plane integrally formed on the plane of the
first sidewall, said tactile feature secured to the first sidewall throughout the rear contact
plane, wherein the first sidewall, the second sidewall, the outer wall, and the tactile
feature are all formed of a single material ~~selected from the group consisting of:~~ of a
metal and a thermoplastic.

2. (Currently amended) The key ~~cover~~ securement of claim 1 wherein the tactile feature is a geometric shape on the first sidewall.

3. (Currently amended) The key ~~cover~~ securement of claim 2 wherein the geometric shape is selected from the group consisting of: a circle, a triangle, a square, a parallelogram, a star, a cross, a house icon, an animal icon, a vehicle icon, and a human icon.

4. (Currently amended) The key ~~cover~~ securement of claim 2 wherein the geometric shape is raised above the plane of the first sidewall.

5. (Currently amended) A key ~~cover for covering a head of a key, where the head has an opening for receiving a key ring therethrough, said key cover~~ securement comprising:

a key;

a key ring; and

a key cover comprising:

a first sidewall defining a plane and terminating in a first edge, the first sidewall having a first aperture ~~therethrough~~ extending through the first sidewall;

a second sidewall terminating in a second edge, the second sidewall having a second aperture ~~therethrough~~ extending through the second sidewall;

an outer wall extending between the first and second sidewalls to define a recess that receives the head of the key therein so that the opening in the head ~~is aligned~~ remains aligned with the key cover only by the key ring passing simultaneously therethrough

wherein the outer wall having ends that are spaced apart from the first and second edges of the first and second sidewalls, respectively;

a tactile feature defining a rear contact plane integrally formed on the plane of the first sidewall, said tactile feature secured to the first sidewall throughout the rear contact plane, wherein the first sidewall, the second sidewall, the outer wall, and the tactile feature are all formed of a single material ~~selected from the group consisting of:~~ of a metal and a thermoplastic;

wherein ~~the~~ a geometric shape is raised above the plane of the first sidewall; and

further comprising a second geometric shape depressed beneath the plane of the first sidewall.

6. (Currently amended) The key ~~cover~~ securement of claim 1 wherein the tactile feature is a raised treatment along the first edge protruding outwardly from the plane of the first sidewall.

7. (Currently amended) The key ~~cover~~ securement of claim 6 wherein the edge treatment is selected from the group consisting of: a repeating row of three-dimensional geometric shapes, a barbell, and a braid.

8. (Currently amended) The key ~~cover~~ securement of claim 1 further comprising a second tactile feature integral with a portion of said key cover selected from the group consisting of: the second sidewall and the second edge.

9. (Currently amended) The key ~~cover~~ securement of claim 8 wherein the tactile feature and the second tactile feature are identical and in opposition.

10. (Canceled)

11. (Currently amended) A key ~~ring~~ securement comprising:

a first key having a first opening therethrough, said first key encompassed by a key cover according to claim 1;

a second key having a second opening therethrough, said second key encompassed by a second key cover according to claim 1 wherein the second key cover has a different tactile feature relative to said first key cover; and

a ~~securement~~ key ring simultaneously engaging the first key opening, the first key cover, the second key opening and the second key cover.

12. (Previously presented) A key cover of claim 1 obtainable by a process comprising the steps of:

casting molten metal into a mold having a void complementary to said key cover of claim 1;

allowing said molten metal sufficient time to solidify into a key cover casting; and
polishing said casting.

13. (Original) A key cover of claim 12 wherein the molten metal is selected from the group consisting of a pure or alloyed form of: aluminum, iron, brass, silver, tin, and zinc.

14. (Original) The key cover of claim 12 produced by a process further comprising the step of: having a textural surface treatment to said key cover.

15. (Original) The key cover of claim 14 wherein the textural treatment is selected from the group consisting of: paint, resin, enamel and an inlay.

16. (Previously presented) A key cover of claim 1 obtainable by a process comprising the steps of:

injection molding thermoplastic into a mold having a void complementary to said key cover of claim 1;

allowing said thermoplastic sufficient time to solidify into a key cover casting; and
polishing said casting.

17. (Previously presented) A key cover of claim 16 wherein the thermoplastic is selected from the group consisting of olefins; polyurethanes; polyesters; polyolefins; aliphatic polyamide; polycarbonate; polyacrylonitrile; polycarbonate; polyvinyl chloride; and polystyrene.

18. (Original) The key cover of claim 16 produced by a process further comprising the step of: having a textural surface treatment to said key cover.

19. (Previously presented) The key cover of claim 18 wherein the textural treatment is selected from the group consisting of: paint, resin, enamel and an inlay.

20-24 (Canceled)